



Index nr	8320050	8320069	8320167	8320234	8320104	8320225	BC 214 BL	BC 79 B	BC 263 B	BC 154	BF 121	BC 148 B	BC 322 B	BC 309 B
							BC 212 BL	BC 252 B	BC 558 B	BC 154	BC 154	BC 158 B	BC 321 B	BC 308 B
													MPS 6519	

- Condensators marked: HK: High-K, KBL: Barrier layer, MF: Metallized film, MK: Metallized paper, PS: Polystyren
- Condensators without specifications: PS: Polystyren, PS: Kondensatorer uden angivelse
- Condensators with specifications: Ceramic, Ceramic, Ceramic
- Resistors without specifications: GBT 1/2W, 10%
- Widerstände ohne Angabe: Modstande uden angivelse
- Subject to change without notice
- Technical changes to be retained
- Ret til ændringer forbeholdes

The voltages specified are negative with respect to chassis and are measured without input-signal with a tube voltmeter.

AF-sensitivities are measured at 500 mW  $\Delta f = 22.5$  kHz,  $f_{mod} = 400$  Hz

FM-IF:  $\Delta f = 22.5$  kHz,  $f_{mod} = 400$  Hz

Die angegebenen Spannungen sind negativ in Bezug auf Masse, und sind ohne Eingangssignal mit einem Röhrevoltmeter gemessen.

NF-Empfindlichkeiten sind bei 50 mW Ausgangsleistung gemessen ( $\nu$  0,45V über  $f_{\Delta}$ )

UKW-ZF:  $\Delta f = 22.5$  kHz,  $f_{mod} = 400$  Hz

De angivne spændinger er negative i forhold til stel, er målt med rørvoltmeter og uden signal.

FM-IF:  $\Delta f = 22.5$  kHz,  $f_{mod} = 400$  Hz

**Bang & Olufsen**

Beolit 500-505, type 1506-1516

Form. 6767

PRINTED IN DENMARK

U.S. EXPORT-TRYKKERIEBET-STRUER

9221018 T-1 C

9221018 T-2

11-74

3531017



